


# KVT-ER

## Split cable glands



Certified protection class  
IP65/IP66/IP67/IP68



Slit KT grommets

### Product description

KVT-ER are split cable glands for routing and sealing cables with and without connectors, conduits or pneumatic hoses with diameters from 1 to 16 mm (KT 1 - 15) and 16 to 35 mm (KT 16 - 34).

Due to the injected gasket and if single-hole grommets are used, the KVT-ER provides certified protection ratings IP65/IP66/IP67/IP68.

The KVT-ER sizes are based on metric standard cut-outs M25, M32, M50 and M63. Hexagonal locknuts are included in the shipment.

For assembly, we recommend to tighten the cover lid screws with max. 2 N m.

### Locknuts

Locknuts with special cut-outs are available separately.



**KGM-SUB-D9** fits D-Sub 9 connectors  
(Required wall cut-out: Ø 36 mm, PU: 10)  
■ Order No. 45106

**KGM-SUB-D25** fits SUB-D25 connectors  
(Required wall cut-out: Ø 50 - 54 mm, PU:10)  
■ Order No. 45110

Description	Type	Order No.	Grommets KT small   large	Thread Thread length	PU
	KVT-ER 25*	45450	1 -	M25 × 1.5 Length: 18 mm	10
	KVT-ER 32	45452	1 -	M32 × 1.5 Length: 18 mm	10
	KVT-ER 50 2	45454	2 -	M50 × 1.5 Length: 20.5 mm	5

\* Max. cable diameter of 15 mm