

KEL-FG-B

Flange enclosures for cable entry



V2A anti-corrosive



Slit KT grommets

Also available with stainless steel screws (V2A).



1.11

Description	Type	Order No.	Grommets small large	PU
	KEL-FG-B4	42330	4 -	1
	KEL-FG-B4 with V2A screws	42330.200	4 -	1
	KEL-FG-B1	42332	- 1	1
	KEL-FG-B1 with V2A screws	42332.200	- 1	1

Product description

The cable entry frames KEL-FG-B are suited for installation, sealing and strain relief of cables with connectors and conduits at an angle of 90° to the cabinet, enclosure or machine wall. A flat rubber gasket is included in the shipment.

Advantages & benefits

- Installation at an angle of 90° to the wall
- Mechanical protection of cable directly at the place of entry
- Protection against water spray and drips
- Warranty on pre-terminated cables remains
- Space saving shape
- Strain relief according to EN 62444
- High stability, vibration resistant

Specifications

Material	Polyamide (PA)
Flame class	UL94-Vo, self-extinguishing
IP rating	IP54, with gasket and correct selection of the cable grommets
Temperature	- 40°C to + 140°C (static)
Properties	Halogen-free, silicone-free
Cut-out dimensions	46 × 36 mm, Page 218 - 219

Accessories

Cable grommets	48 - 52
KEL-EMC Cable collectors	138 - 140
ST Plugs	53