KEL-DPF

Cable entry grommets





The KEL-DPF was developed particularly for routing large or unknown sizes of cables into a switch cabinet or machine (max. cable diameter 70 mm). Due to the flexibility and unique pyramid shape, cable entry and flexible positioning is much easier compared to using conventional cable glands.

Also perfect for bundling or restraining large cables.

Cutting of DPF grommets:

Cable diameter less 25%. The corresponding diameters are marked on the grommet.

It is recommended that additional strain relief be provided for cables as part of the installation.

Advantages & benefits

- Quick and tool-free assembly
- It is possible to install rigid cables at angles
- Suitable for metric cut-outs
- Polyamide locknuts are included in the shipment

Specifications

Material	Thread frame: Polyamide	(PA)

Pyramid: Elastomer

Colour grey (similar RAL 7035)

■ black

Flame class UL94-Vo, self-extinguishing IP rating IP66/IP68 (certified acc. to EN 60529)

UL type rating UL type 12 (acc. to UL 50E)

UL type 4X (acc. to UL 50E)

Temperature 40°C to + 90°C (static) Halogen-free, silicone-free **Properties**

Thread length 14 mm Cut-out dimensions Metric sizes

Accessories

FP Flanged plates 178 - 183 MP Module plates 174 - 175



Туре	Order No.	Thread metric	External diameter	Clamping range	PU
KEL-DPF 25 3-12	42652 50652	M25 × 1.5	39 mm	3 - 12 mm	5
KEL-DPF 32 6-18	42653 50653	M32 × 1.5	46 mm	6 - 18 mm	5
KEL-DPF 40 12-27	42654 50654	M40 × 1.5	54 mm	12 - 27 mm	5
KEL-DPF 50 22-36	42655 50655	M50 × 1.5	64 mm	22 - 36 mm	5
KEL-DPF 63 27-50	■ 42656 ■ 50656	M63 × 1.5	77 mm	27 - 50 mm	5
KEL-DPF 75 39-60	42657 50657	M75 × 1.5	89 mm	39 - 60 mm	1
KEL-DPF 85 48-70	42658 50658	M85 × 2	99 mm	48 - 70 mm	1

Wrenches

for M75/M85 plastic locknuts

For mounting the new KEL-DPF sizes we offer suitable wrenches with widths for M75 and M85 plastic locknuts. Material: aluminium

M75: Order No.61436 | M85: Order No. 61437 | PU: 1



