

# KEL-QTA

## Split cable entry plates



### Product description

The KEL-QTA easily routes pre-terminated cables, multi-conductors, hoses or conduits without using any tools for assembly.

### Advantages & benefits






- Quick assembly without tools
- High cable density by using multi-position grommets
- Simple assembly and disassembly in case of change or service
- Routing of cables with and without connectors in a high density
- Suitable for standard industrial connector cut-outs

### Specifications

**Material** Elastomer  
**Flame class** UL94-Vo, self-extinguishing  
**IP rating** IP54, with correct selection of the cable grommets QT  
**Temperature** - 40°C to + 90°C (static)  
**Properties** Halogen-free, silicone-free  
**Type A:** For wall thickness 1.5 - 2.5 mm  
**Type B:** For wall thickness 2.8 - 4 mm

### Accessories

QT Cable grommets 66  
 ST-B Plugs 85  
 FP Flange plates 178 - 183

Description	Type	Order No. Type A	Order No. Type B	Cut-out [mm]	Cables	PU
	KEL-QTA 24 2 -DP 18	43642	43643	112 × 36	pre-terminated 2 × 1 - 15 mm without connector 16 × max. 7 mm 1 × max. 12 mm 1 × max. 16 mm	10
	KEL-QTA 24 4	43644	43645	112 × 36	pre-terminated 4 × 1 - 15 mm	10
	KEL-QTA 10 1 -DP 18	43655	43658	65 × 36	pre-terminated 1 × 1 - 15 mm without connector 18 × max. 5 mm	10
	KEL-QTA 10 2 -DP 6	43656	43659	65 × 36	pre-terminated 2 × 1 - 15 mm without connector 6 × max. 5 mm	10
	KEL-QTA-B4	43660	-	46 × 46	pre-terminated 4 × 1 - 15 mm	10