

# KEL-ER 24

## Cable entry frames



V2A anti-corrosive



Also available with threaded bushings.






Slit KT grommets



**IP66**

1.11

Description	Type	Order No.	Grommets small   large	PU
	KEL-ER 24 10	48241	10 -	10
	KEL-ER 24 10 with V2A screws	48241.200	10 -	10
	KEL-ER 24 7	48247	6 1	10
	KEL-ER 24 7 with V2A screws	48247.200	6 1	10
	KEL-ER 24 4	48244	2 2	10
	KEL-ER 24 4 with V2A screws	48244.200	2 2	10

### Product description

Split cable entry system for routing and sealing cables with connectors, providing an IP66 / up to UL type 4X rating and strain relief for cable diameters from 1 to 16 mm (KT 1 - 15) and 16 to 35 mm (KT 16 - 34).

The new cable entry system is easy to install. Cable grommets are placed into compartments and are securely fixed to the frame during assembly. The KEL-ER 24 frame matches exactly the dimensions for 24-pin standard industrial connectors. A flat rubber gasket is included in the shipment.

### Advantages & benefits

- Warranty on pre-terminated cables remains
- Retrofits, repairs and maintenance can be done much more easily and quickly
- High cable density, wide variety of grommets
- Strain relief according to EN 62444
- High stability, vibration resistant

### Specifications

Material	Polyamide (PA)
Flame class	UL94-Vo, self-extinguishing
IP rating	IP66, with gasket and correct selection of single grommets (certified acc. to EN 60529)
UL type rating	UL type 4X (acc. to UL 50E)
Temperature	- 40°C to + 140°C (static)
Properties	Halogen-free, silicone-free
Cut-out dimensions	36/46 × 112 mm / page 218 - 219
Frame depth	17 mm

### Accessories

KT Cable grommets	48 - 50
KEL-EMC Cable collectors	138 - 140
ST Plugs	53