

# KEL-DPZ 24

## Cable entry plates



Also available in black.



Also available with threaded bushings.



Membrane on front

### Product description

2.1





KEL-DPZ entry plates are designed to route and seal up to 121 cables without connectors or fibre optics (from 1.5 mm to 22 mm in diameter) in limited space.

The KEL-DPZ products are a cost and time saving alternative to traditional cable glands.

The assembly of the KEL-DPZ 24 with cables or pneumatic hoses can be done quick and easy. Simply make a small hole in the thin membrane, push the cables through. The KEL-DPZ 24 provides strain relief and protection up to IP66 / UL type 12.

The size DPZ 24 matches exactly the cut-out dimensions of 24-pin standard industrial connectors.

ST-B Plugs can be used for sealing pierced membranes if cables have been removed.

Description	Type	Order No.	Number of cables	PU
	KEL-DPZ 24 14	■ 43700 ■ 50700	10× 3.2 - 6.5 mm 4× 16 - 22 mm	10
	KEL-DPZ 24 15	■ 43720 ■ 50720	15× 7.2 - 12 mm	10
	KEL-DPZ 24 16	■ 43725 ■ 50725	8× 3.2 - 6.5 mm 4× 5 - 9.7 mm 2× 9 - 16.2 mm 2× 16 - 22 mm	10
	KEL-DPZ 24 17	■ 43705 ■ 50705	6× 3.2 - 6.5 mm 6× 5 - 10.2 mm 5× 9 - 16.2 mm	10

\* Only valid for grey product types