

KEL-DPZ-E

Cable entry plates





Conical shape on back provides additional sealing and strain relief



Also available in black.



Description	Type	Order No.	Number of cables	PU
	KEL-DPZ-E 112 7	 43780 50780	7 × 7.5 - 12 mm	10
	KEL-DPZ-E 112 21	 43790 50790	21 × 3.2 - 6.5 mm	10

* Only valid for grey product types

Product description

KEL-DPZ-E is designed for routing cables without connectors without connectors in very small space.

The assembly of the KEL-DPZ-E with cables or pneumatic hoses can be done quick and easy. Simply make a small hole in the thin membrane, push the cables through. The KEL-DPZ-E provides strain relief and protection IP66 / UL type 12.

With an area of only 18 × 112 mm, up to 21 cables can be easily routed and sealed.

ST-B Plugs can be used for sealing pierced membranes if cables have been removed.

Advantages & benefits

- Space saving shape
- Dual sealing of cables acc. to IP66/UL type 12
- High cable density
- Fast and easy assembly
- Hygienic design

Specifications

Material	Frame: Polyamide (PA) Sealing plate: Elastomer
Colour	 grey (similar RAL 7035) black
Flame class	UL94-Vo, self-extinguishing
IP rating	IP66 (certified acc. to EN 60529)
UL type rating	UL type 12 (acc. to UL 50E)
Temperature	- 40°C to + 90°C (static)
Properties	Halogen-free, silicone-free
Cut-out dimensions	18 × 112 mm / page 218 - 219
Plate depth	14 mm

Accessories

ST-B Plugs	85
KEL-EMC-PF Cable collectors	139

2.1