

KEL 24-MT

Extended cable entry frames



V2A anti-corrosive








Also available with threaded bushings.



IP54

1.11

Description	Type	Order No.	Grommets small large	PU
	KEL 24 20-MT	42232	20 -	1
	KEL 24 20-MT with V2A screws	42232.200	20 -	1
	KEL 24 17-MT	42224	16 1	1
	KEL 24 17-MT with V2A screws	42224.200	16 1	1
	KEL 24 14-MT	42225	12 2	1
	KEL 24 14-MT with V2A screws	42225.200	12 2	1
	KEL 24 11-MT	42222	8 3	1
	KEL 24 11-MT with V2A screws	42222.200	8 3	1
	KEL 24 8-MT	42221	4 4	1
	KEL 24 8-MT with V2A screws	42221.200	4 4	1

Product description

The cable entry frame KEL 24-MT provides additional cable routing possibilities.

The KEL 24-MT series are KEL frames extended with an additional middle frame for routing additional cables. Thus allowing the quick, easy and cost effective routing solution for up to 80 cables.

A flat rubber gasket is included in the shipment.

Advantages & benefits

- Warranty on pre-terminated cables remains
- Retrofits, repairs and maintenance can be done much more easily and quickly
- High cable density
- Strain relief according to EN 62444
- High stability, vibration resistant

Specifications

Material	Polyamide (PA)
Flame class	UL94-Vo, self-extinguishing
IP rating	IP54, with gasket and correct selection of the cable grommets (certified acc. to EN 60529)
Temperature Properties	-40°C to +140°C (static)
Cut-out dimensions	82 × 112 mm / Page 218 - 219
Frame depth	17 mm

Accessories

KEL-SNAP Mounting frames	31
Cable grommets	48 - 52
KEL-EMC Cable collectors	138 - 140
ST Plugs	53