

KEL 16-2MT

Extended cable entry frames



V2A anti-corrosive

Also available with stainless steel screws (V2A).






Also available with threaded bushings.



IP54

1.11

Description	Type	Order No.	Grommets small large	PU
	KEL 16 24-2MT	42149	24 -	1
	KEL 16 24-2MT with V2A screws	42149.200	24 -	1
	KEL 16 12-2MT	42148	8 4	1
	KEL 16 12-2MT with V2A screws	42148.200	8 4	1
	KEL 16 6-2MT	42147	- 6	1
	KEL 16 6-2MT with V2A screws	42147.200	- 6	1

Product description

The KEL 16-2MT is our largest frame providing the ability to route and seal up to 96 cables.

The cable entry frames KEL 16-2MT series are KEL 16 frames extended with two additional middle frames for routing additional cables. Thus allowing the quick, easy and cost effective routing solution for up to 96 cables. A flat rubber gasket is included in the shipment.

Advantages & benefits

- Warranty on pre-terminated cables remains
- Retrofits, repairs and maintenance can be done much more easily and quickly
- High cable density
- Strain relief according to EN 62444
- High stability, vibration resistant

Specifications

Material	Polyamide (PA)
Flame class	UL94-Vo, self-extinguishing
IP rating	IP54, with gasket and correct selection of the cable grommets (certified acc. to EN 60529)
Temperature	-40°C to + 140°C (static)
Properties	Halogen-free, silicone-free
Cut-out dimensions	126 × 86 mm
Frame depth	17 mm

Accessories

Cable grommets	48 - 52
KEL-EMC Cable collectors	138 - 140
ST Plugs	53